CIVIL ENGINEERING APPLICATIONS USING TDA

PRESENTED BY:

Joaquin Wright, GHD Inc.

On Behalf of CalRecycle

TO:

ASCE Redwood Empire Branch

3/12/20









Todays Presentation

- Introduction to TDA use in Civil Engineering Applications Video
- Civil Engineering Applications in California Project Summaries
- CalRecycle TDA Grant Outline







CalRecycle's Objective is to promote the use of TDA in Civil Engineering Applications

- Educate Local Public Works, CALTRANS, Private Consulting Civil Engineers and State and Local Environmental Agencies on the benefits of TDA
- Research Develop Sustainable, Environmental Beneficial and Cost Effective Civil Engineering Reuses for Waste Tires
- Coordinate and Assist Waste Tire Processors to assure there is adequate TDA to meet future demand.







Beneficial Properties of Tire Derived Aggregate (TDA) in Civil Engineering Applications

- Tire Derived Aggregate (TDA) has properties that civil engineers, public works directors & contractors need
 - Lightweight
 - Free Draining/High Permeability
 - Low earth pressure
 - Good thermal insulation
 - Durable
 - Compressible
 - May be cheapest solution
 - Helps the environment when used in sustainable infrastructure
 - Conserve natural aggregate resources







Uses for Tire Derived Aggregate


- Lightweight fill for Road Embankments
- Lightweight backfill for Retaining Walls
- Lightweight fill for Road Slide Repair
- TDA used in Vibration Mitigation Applications
- TDA in Storm-Water infiltration galleries
- TDA in Landfill Applications
- TDA in ??








Caltrans Embankment Projects with TDA

















Caltrans Embankment Projects with TDA






Dixon Landing/HWY 880 Interchange Project
















101 Re-alignment Project, Caltrans







Highway 101, Confusion Hill - Lightweight TDA Embankment Project 2008







Confusion Hill - Lightweight TDA Embankment Project 2008



Confusion Hill - Lightweight TDA Embankment Project 2008







Highway 101 Confusion Hill project Final Condition



Caltrans Route 60/215/91 Interchange TDA Backfill Behind Retaining Walls













Riverside, CA




Type 1 T Retaining Walls



Estimated Savings on Future Walls - \$200/ lineal foot



Type 1 TDA Retaining Wall








presenting beneficial and cost effective uses of TDA

Ortega Ridge Road Repair









Ortega Ridge Road Repair









Ortega Ridge Road Repair









Ortega Ridge Road Repair









Ortega Ridge Road Repair









Ortega Ridge Road Repair










Yuba County road failure repairs with TDA





Yuba County road failure repairs with TDA









Yuba County road failure repairs with TDA









Yuba County road failure repairs with TDA









CalRecycle TDA Leader Project

Yuba County road failure repairs with TDA










Tuolumne County Road Failure Repairs









Tuolumne County Road Failure Repairs









Tuolumne County Road Failure Repairs









Tuolumne County Road Failure Repairs









Tuolumne County Road Failure Repairs

Footing for Gabion Basket Walls backfilled with TDA, Italian Bar Road Site #5












Slide Repair Projects

- 2007 Marina Drive, Mendocino Co. Landslide Repair
- 2008 Sonoma Co. Geysers Rd. Landslide Repair Project
- 2009 Sonoma Mtn. Road , Landslide Repair Project





Marina Drive Slide Repair







Mendocino County, Marina Dr.









Marina Drive Slide Repair







Geysers Road Slide



Geysers Road Slide Repair











Geysers Road

Before

Savings to County \$128,000







UPPER PERFORMANCE

Sonoma Mtn. Road, Sonoma County












Sonoma Mtn. Road, Sonoma County









TDA Vibration Attenuation in California







TDA for Vibration Attenuation

Factors for TDA Usage

- Geotechnical data
- Proximity and height of nearby buildings
- Targeted vibration frequency ranges
- TDA underlayment provides significant reduction to rail frequencies above 16 Hz




Image Source: RIVAS (http://www.rivas-project.eu)

 Alternative to traditional floating concrete slabs

























TDA Underlayment

- 1-foot thick TDA
- Non-woven filter fabric for drainage and separation, installed on top and bottom of TDA
- Compacted with 10-ton vibratory roller (6 passes)





Valley Transportation Authority(VTA) BART Berryessa Extension



- Construction
 - Commenced in 2012
 - Passenger service anticipated for 2018
 - Contractor: Skanska Shimmick Herzog Joint Venture (SSHJV)








TDA Sections

- 4 separation phases
- Length of TDA sections combined totaled over 1 mile (5,550 feet)


















































- Installed using standard construction methodologies
- Density: 46 lb/CF ±10% (41 to 50 lb/CF)









Construction Schedule and Cost

- Average TDA placement productivity:
 - 110 linear foot track per day
 - 130 cubic yards of TDA per day
- Cost Comparison

Cost Comparison	TDA Underlayment	Floating Concrete Slab
Total Cost for 5,500 LF track	\$ 350,000 ⁺	\$ 4,026,000*

• Per the Federal Transit Administration, 2006, for cost per linear foot track; listed value accounts for inflation and market conditions for 2017

* Reported by SSHJV, includes labor, materials, and equipment









Savings to VTA/ BART: \$3,676,000







TDA LID Designs


- Butte Regional Transit Operations Center (BRTOC), Chico, CA
 - Butte County Association of Governments
 - Construction Complete in 2016
- Fleet and Materials Lab Building, Santa Rosa, CA
 - County of Sonoma
 - Construction Complete in 2016
- Transportation Improvements for Redwood Business Park, Ukiah, CA
 - City of Ukiah
 - In Construction now








BRTOC Project Site Plan





Bioretention Swale Typical Section













































































Sonoma County Fleet Facility Site Plan



AGGREGATE



Bioretention Swale Typical Section




































































City of Ukiah Redwood Business Park Typical Road Reconstruction & LID Plan











TDA Infiltration gallery cross section view



Typical Infiltration Gallery (Pre-Construction)









Typical Infiltration Gallery (Storm Water)









Typical Infiltration Gallery (excavation & fill)









Typical Infiltration Gallery

















- Grant Amount: \$350,000 Maximum (\$750k for large TDA use projects)
- Eligible Applicants
 - Local Governments (cities and counties)
 - Special Districts
 - State Agencies
 - Qualifying Indian Tribes
 - Private, for-profit entities







Eligible Projects/Categories

- Lightweight fill (slope stabilization, embankment fill, ...)
- Vibration mitigation (under light rail lines)
- Low impact development (LID) / Storm water management
- Aggregate replacement projects in landfills







- Project Requirements
 - 100% CA-generated waste tires
 - Minimum 500 tons of TDA materials (200 tons for LID projects)
 - Plans and specifications are subject to review by CalRecycle's engineering staff
 - Technical assistance/training will be provided by CalRecycle contractors and/or staff







Eligible Reimbursement Costs

- TDA material
- Transportation
- Installation (\$7.5 per ton max)
- Testing (5k max)
- Engineering/Design Work (additional 13% 50%, depending on project)







Grant Program Overview

• How to apply?

TDA Grant Webpage:

www.calrecycle.ca.gov/Tires/Grants/TDA

Date	Activity
April 2019	Application Release
August 2019 November 2019 February 2020	Application Due Dates
September 2019 December 2019 March 2020	Secondary Due Dates (for Resolutions, Environmentally Preferable)
October 2019 January 2020 April 2020	Grant Awards
April 1, 2022	Grant Term Ends

TDA Grant contact, Loreto Tamondong

(916) 341-6464, or e-mail: Loreto.Tamondong@CalRecycle.ca.gov













